

Diamond Seat Mounting Guidelines

All seats are mounted differently due to drivers preferences. However, these tips are to help you mount your seat the safest way.

2 different Mounting Points – Make sure to use only 3/8” Grade-8 Bolts, heavy duty large hardened flat washers and lock nuts at all mounting points

*To start place the seat in the car and position to your most comfortable position.

*We have a double plate in the back of the seat which is the safest location to mount from. Make a 1/4” aluminum or 1/8” steel 90 degree bracket, attach with 3/8” bolts.

*For bottom mount use (2) 1/4” aluminum/steel brackets or 1” .090 steel tubing welded to chassis in each location and attach with bolts, nuts and washers straight through bottom of the seat.

Use only 3/8”
Grade-8 Bolts



*The Joie
of Seating*

4537 Orphanage Rd. Concord, NC 28027 (704) 795-7474
www.thejoieofseating.com

Custom Seat Mounting Guidelines (All Belts to Seat – Top 3 NASCAR Divisions)

All seats are mounted differently due to drivers preferences. However, these tips are to help you mount your seat the safest way.

3 different Mounting Points – Make sure to use only 3/8" Grade-8 Bolts, heavy duty large hardened flat washers and lock nuts at all mounting points

*To start place the seat in the car and position to your most comfortable position.

*We have holes in 3 different locations for mounting purposes. Start with the 3 holes in the top back of the seat. Make a 1/4" aluminum or steel 90 degree bracket, attach with 3/8" bolts.

Use only 3/8"
Grade-8 Bolts

*For hip mounts and front side mounts in the seat use (2) 1/4" aluminum or steel brackets welded to chassis in each location and attach with bolts, nuts and washers to the 2 bung holes provided.



*The Joie
of Seating*

4537 Orphanage Rd. Concord, NC 28027 (704) 795-7474
www.thejoieofseating.com

Custom Sprint Seat Mounting Guidelines

All seats are mounted differently due to drivers preferences. However, these tips are to help you mount your seat the safest way.

2 different Mounting Points – Make sure to use only 3/8” Grade-8 Bolts, heavy duty large hardened flat washers and lock nuts at all mounting points

*To start place the seat in the car and position to your most comfortable position.

*We have 2 mounting bungs in the back of the seat which is the safest location to mount from. Make a 1/4” aluminum or steel 90 degree bracket, attach with 3/8” bolts.

*For bottom mount as far forward as possible use (2) 1/4” aluminum/steel brackets or 1” .090 steel tubing welded to chassis in each location and attach with bolts, nuts and washers straight through bottom of the seat.



Use only 3/8”
Grade-8 Bolts

*The Joie
of Seating*

4537 Orphanage Rd. Concord, NC 28027 (704) 795-7474
www.thejoieofseating.com